Heat Transfer Asian Research
Subject Index to Volume 29, 2000

2-D Lennard-Jones (LJ) fluid: **3**, 218-232

Absorption: **5**, 427-445
Absorption refrigeration: **7**, 581-597
Active ephemeral wave: **1**, 1-14
Air-water two-phase flow: **5**, 412-426
Anisotropic porous matrix: **5**, 373-384

Bioengineering: **1**, 34-44
Body force effect: **6**, 512-522
Boiling: **1**, 45-58; **3**, 193-203, 204-217; **6**, 447-458, 459-472, 523-534; **8**, 634-647, 648-659
Bubble: **3**, 193-203; **6**, 459-472
Burnout: **6**, 459-472

Cluster: **3**, 218-232
Coefficient of performance: **6**, 473-490
Cold thermal energy: **4**, 249-268
Colloidal particle: **3**, 166-180
Combined convective and radiative heat transfer: **5**, 385-399
Combined cycle: **5**, 347-357
Computational fluid dynamics: **6**, 512-522
Concentration: **4**, 317-332
Condensation: **3**, 204-217; **4**, 269-279; **6**, 523-534; **8**, 634-647, 648-659
Condensation inside horizontal tube: **8**, 623-633
Convective heat transfer: **6**, 512-522; **7**, 573-580
Convective power: **7**, 573-580
Cooling performance: **3**, 204-217
Critical heat flux: **2**, 132-143, 144-154; **6**, 447-458
Critical heat transport rate: **1**, 59-71
Critical wavelength: **2**, 132-143

Cryogenics: **5**, 347-357
Crystal growth: **2**, 120-131
Crystallization: **3**, 166-180

Density: **3**, 181-192
Disperse system: **7**, 535-544
Dissociated steam: **3**, 181-192
Double-effect: **5**, 427-445
Dry ice: **4**, 249-268
Drying: **5**, 385-399
Dual heat sources: **6**, 473-490

Effective heated length: **2**, 144-154
Effective thermal conductivity: **6**, 491-497
Eggcrate support plate: **2**, 91-112
Electric field: **4**, 269-279
Electrical switching: **3**, 155-165
Electronics cooling: **4**, 333-346
Ellipsoidal liquid film: **4**, 280-299
Endothermic phenomenon: **8**, 609-622
Energy saving: **6**, 473-490
Energy storage: **4**, 300-316; **5**, 347-357
Enhancement ratio: **4**, 269-279
Ephemeral wave: **1**, 1-14
Evaporator: **6**, 473-490

Falling liquid film: **3**, 233-248
Film boiling: **4**, 280-299
Filtration coefficient: **1**, 72-90
Flow field: **3**, 233-248
Flow rate density: **4**, 280-299
Flow visualization: **3**, 155-165; **4**, 333-346
Fluctuating pressure: **5**, 412-426
Fluidized bed: **7**, 598-608
Forced convection: **1**, 45-58; **5**, 385-399
Fountain pressure: **1**, 15-21
Fractal: **6**, 491-497; **7**, 535-544

Heat Transfer Asian Research
Subject Index to Volume 29, 2000

2-D Lennard-Jones (LJ) fluid: **3**, 218-232

Absorption: **5**, 427-445
Absorption refrigeration: **7**, 581-597
Active ephemeral wave: **1**, 1-14
Air-water two-phase flow: **5**, 412-426
Anisotropic porous matrix: **5**, 373-384

Bioengineering: **1**, 34-44
Body force effect: **6**, 512-522
Boiling: **1**, 45-58; **3**, 193-203, 204-217; **6**, 447-458, 459-472, 523-534; **8**, 634-647, 648-659
Bubble: **3**, 193-203; **6**, 459-472
Burnout: **6**, 459-472

Cluster: **3**, 218-232
Coefficient of performance: **6**, 473-490
Cold thermal energy: **4**, 249-268
Colloidal particle: **3**, 166-180
Combined convective and radiative heat transfer: **5**, 385-399
Combined cycle: **5**, 347-357
Computational fluid dynamics: **6**, 512-522
Concentration: **4**, 317-332
Condensation: **3**, 204-217; **4**, 269-279; **6**, 523-534; **8**, 634-647, 648-659
Condensation inside horizontal tube: **8**, 623-633
Convective heat transfer: **6**, 512-522; **7**, 573-580
Convective power: **7**, 573-580
Cooling performance: **3**, 204-217
Critical heat flux: **2**, 132-143, 144-154; **6**, 447-458
Critical heat transport rate: **1**, 59-71
Critical wavelength: **2**, 132-143

Cryogenics: **5**, 347-357
Crystal growth: **2**, 120-131
Crystallization: **3**, 166-180

Density: **3**, 181-192
Disperse system: **7**, 535-544
Dissociated steam: **3**, 181-192
Double-effect: **5**, 427-445
Dry ice: **4**, 249-268
Drying: **5**, 385-399
Dual heat sources: **6**, 473-490

Effective heated length: **2**, 144-154
Effective thermal conductivity: **6**, 491-497
Eggcrate support plate: **2**, 91-112
Electric field: **4**, 269-279
Electrical switching: **3**, 155-165
Electronics cooling: **4**, 333-346
Ellipsoidal liquid film: **4**, 280-299
Endothermic phenomenon: **8**, 609-622
Energy saving: **6**, 473-490
Energy storage: **4**, 300-316; **5**, 347-357
Enhancement ratio: **4**, 269-279
Ephemeral wave: **1**, 1-14
Evaporator: **6**, 473-490

Falling liquid film: **3**, 233-248
Film boiling: **4**, 280-299
Filtration coefficient: **1**, 72-90
Flow field: **3**, 233-248
Flow rate density: **4**, 280-299
Flow visualization: **3**, 155-165; **4**, 333-346
Fluctuating pressure: **5**, 412-426
Fluidized bed: **7**, 598-608
Forced convection: **1**, 45-58; **5**, 385-399
Fountain pressure: **1**, 15-21
Fractal: **6**, 491-497; **7**, 535-544

Free surface flow: **3**, 233-248
Freezing: **4**, 249-268, 300-316
Frequency: **5**, 358-372

Gas radiation: **5**, 385-399
Gas turbine: **5**, 347-357
Geothermal energy: **5**, 373-384

Heat exchanger: **2**, 91-112; **7**, 598-608
Heat pipe: **1**, 59-71, 72-90; **4**, 317-332; **7**, 559-572
Heat pump: **6**, 473-490; **8**, 660-673
Heat transfer: **1**, 15-21, 45-58, 59-71; **2**, 91-112; **3**, 233-248; **4**, 249-268, 280-299, 333-346; **5**, 373-384, 385-399, 400-411; **6**, 459-472; **7**, 545-558, 559-572, 581-597, 598-608
Heat transfer coefficient: **1**, 22-33; **8**, 623-633
Heat transfer enhancement: **4**, 269-279; **5**, 358-372
Heat transport: **4**, 317-332
Heat transport rate: **7**, 559-572
Helical blade: **8**, 660-673
Helmholtz instability: **2**, 132-143
Horizontal channel: **6**, 459-472
Horizontal low-finned tube: **4**, 269-279
Hot mill: **4**, 280-299
Hot water supply: **6**, 473-490
Hydrogen bond: **3**, 218-232
Hydrostatic pressure: **1**, 15-21

Impinging spray jet: **4**, 280-299
Implicit scheme: **5**, 400-411
Inactive ephemeral wave: **1**, 1-14
Initial concentration: **1**, 59-71
Internal mass source: **3**, 166-180
Inverse heat conduction problem: **2**, 113-119
Inversion point temperature: **5**, 385-399

j-factor: **2**, 91-112

Laminar flow: **6**, 512-522
Latent heat: **5**, 400-411
Linearization of source term: **5**, 400-411
Liquefied natural gas (LNG): **4**, 249-268
Liquid: **7**, 598-608
Liquid air: **5**, 347-357
Liquid drop: **6**, 498-511
Liquid ring compressor: **8**, 660-673
Local condensing heat transfer coefficient: **8**, 623-633
Low Grashof number: **8**, 609-622
Low-pressure conditions: **1**, 22-33

Main wave-vein: **1**, 1-14
Maragnoni convection: **7**, 581-597
Mass diffusivity: **1**, 72-90
Mass transfer: **1**, 72-90; **4**, 317-332; **7**, 559-572, 581-597
Microlayer: **3**, 193-203
Mixing model: **5**, 412-426
Molecular dynamics: **3**, 218-232
Molecular simulation: **3**, 181-192
Monte Carlo method: **3**, 181-192
Multi-stacked radiator cores: **8**, 634-647, 648-659
Multiphase flow: **1**, 1-14, 45-58; **3**, 155-165; **5**, 412-426

Natural convection: **2**, 120-131; **4**, 300-316, 333-346; **5**, 358-372, 373-384; **7**, 545-558; **8**, 609-622
Natural convective boiling in tube: **6**, 447-458
Network: **3**, 218-232
Nonlinear: **2**, 113-119
Nonuniform heat flux: **2**, 144-154
Nuclear engineering: **5**, 412-426
Nuclear reactor: **5**, 412-426
Numerical analysis: **1**, 45-58; **3**, 233-248; **4**, 300-316; **7**, 545-558; **8**, 609-622
Numerical study: **5**, 385-399

Optical thickness: **5**, 385-399
Oscillation: **6**, 523-534
Osmosis: **1**, 59-71, 72-90; **4**, 317-332; **7**, 559-572
Osmotic area: **7**, 559-572

Osmotic coefficient: **1**, 72-90

Parallel flow: **2**, 91-112
Parallel plate channel: **4**, 333-346
Percolation: **7**, 535-544
Performance estimation: **2**, 91-112
Perfusion rate: **1**, 34-44
Phase change: **6**, 498-511
Phonon: **7**, 573-580
Photographic study: **6**, 498-511
Pipe flow: **1**, 1-14; **6**, 512-522
Porous medium: **4**, 300-316; **5**, 373-384; **6**, 447-458, 491-497
Power plant: **5**, 347-357
Power spectrum: **7**, 545-558
Pressure drop: **2**, 91-112
Pressure wave: **6**, 498-511
PVT properties: **3**, 181-192

Refrigerant: **6**, 473-490
Refrigerant circulation: **3**, 204-217
Roll cell: **4**, 333-346
Rotating roll: **4**, 280-299

Secondary flow: **6**, 512-522
Self-excited: **6**, 523-534
Shell side: **2**, 91-112
Simulation: **5**, 427-445
Solid: **7**, 598-608
Solid fraction: **2**, 120-131
Solidification: **2**, 120-131; **4**, 249-268
Solidification ratio: **5**, 400-411
Solution flow rate: **4**, 317-332
Square enclosure: **7**, 545-558
Stability: **7**, 581-597
Standing wave: **5**, 358-372
Start-up characteristics: **5**, 427-445
Stefan problem: **5**, 400-411
Sub-wave-vein: **1**, 1-14
Subchannel cross flow: **5**, 412-426
Subcooled flow boiling: **2**, 144-154
Supercooled flow boiling: **2**, 132-143
Superfluid helium: **1**, 15-21
Superheated steam: **5**, 385-399
Surface tension: **7**, 581-597

Temperature field: **3**, 233-248
Thermal analysis: **4**, 280-299
Thermal conductivity: **7**, 535-544
Thermal engineering: **6**, 498-511
Thermal expansion valve: **6**, 473-490
Thermal radiation: **5**, 385-399
Thermodynamics: **3**, 181-192
Thermophysical properties: **3**, 181-192
Thermophysical property: **1**, 72-90
Thermosyphon: **3**, 204-217; **6**, 523-534; **8**, 634-647, 648-659
Three-dimensional inner microfin tube: **8**, 623-633
Tissue properties: **1**, 34-44
Truly dissolved impurity: **3**, 166-180
Turbulent convective mass transfer: **3**, 166-180
Two-dimensional: **2**, 113-119

Ultrafast CT scanner: **3**, 155-165
Ultrasonics: **5**, 358-372
Unsteady flow: **3**, 155-165

van der Waals pressure: **1**, 15-21
Vapor dome: **6**, 459-472
Vapor explosion: **6**, 498-511
Vertical thick plate: **8**, 609-622
Vibration: **7**, 545-558
Void distribution: **3**, 155-165
Void fraction: **7**, 598-608

Waste heat recovery: **5**, 427-445
Water: **3**, 218-232
Water evaporation: **1**, 22-33
Wave: **1**, 1-14; **3**, 233-248
Wave-vein analysis: **1**, 1-14

X-ray: **3**, 155-165